




Milk Procurement Solution

Android Mobile AMCU by **Hindustan Thermostatics**

PROPOSED DATA FLOWCHART





ULTRA SCAN SWIFT IOT BOND





ULTRA SCAN MILCH ANALS

Monday 10 Oct. 2019 Most unique product in its class which gives results in just 18 secs and server data sync within 0.9 sec



BLUETOOTH CONNECTIVITY

Just plug and play Bluetooth connectivity for seamless data capturing



CONNECTIVITY

Data output via Bluetooth & use your own android cell phone to capture & save data



Swift Milk Analyzer + Ultrasonic Stirrer +100 Kg Electronic Weighing Scale+ Thermal Printer + Android APP + 3 Year Web Server + 1000 Sms





DPU REPLACED BY mAMCU






✓ We are not using any conventional DPU for processing milk collection data.

✓ All calculation and data is processed only in Mobile Application itself.


EMM (ENTERPRISE MOBILE MANAGEMENT)




Lock & Wipe Feature



Reset/Clear Passcode



Single/ Multi Application Mode



- √ 256-bit AES encryption enabled
- ✓ Lost Mode
- ✓ Device Inventory Data


- ✓ Two-factor Authentication
- √ Geo Tagging

POWERED BY






Control/Customize your Android Device with multiple enterprise solutions




Farmer Mobile App



Supervisor App




Collection App



MOBILE APP






Ш

0

MOBILE APP

Milk Dispatch






Dispatch QRCODE for the tanker driver



MAINTENANCE






Repor	t an Issi	ue	:
Select issue t Describe you		efly	>
		<u>()</u>	
Attach Pho	otos	Click Photos	
	ubmit Pr		

MAMCU ADMIN PANEL

- √ Tally Sheet Management / Ledger Management
- ✓ Shift Management
- ✓ Auto Mode Lock/Un-Lock (Auto/Manual Collection Mode)
- ✓ Shift-wise Periodic Report Generation
- ✓ Realtime Collection Data Update to RMPS Server
- ✓ Agency Collection With / Without integration with Scale & Analyzer
- ✓ RCD Process and Data Update to Server
- ✓ Agency Periodic Report Generation
- Collection Management and reporting for all type of collectors (Agency, Large Farmers & Chilling Center)
- Edit/Delete Milk collection Entry Reports for Automatic/Manual collection.



CLOUD SECURITY COMPLIANCE











ISO 27001:2013 certification

Regular VAPT Valuation

All data on TLS/SSL secured channels







PCI Compliance

Cloudflare Powered 2 Factor Authentication Enterprise Level DDoS protection.



Amazon Cognito based authentication to provide PCI DSS, SOC, and ISO/IEC 27001, ISO/IEC 27017, ISO/IEC 27018, and ISO 9001 compliant.

POWERFUL BACKEND





Amazon RDS Enterprise servers for hosting and data storage to provide database encryption and security



AWS Coginito based ISO/IEC 27001 level 2 factor Authentication



Amazon EC2 server with VPC (Virtual Private Cloud)
Network



Built on Node.js, Gold standard for Enterprise Level Web Application



Optimized for high-latency or unreliable networks (2G / 3G)



Battel Tested Architecture used by the likes of Netflix, Facebook and Linkedin

More Convenient WINNER with less expensive with HINDUSTAN more convenience THERMOSTATICS **Double IOT Bridge Ultra Scan** Sensor **Swift Analyzer** works Offline & Online, Fastest Analyzer Handshake with Results in 25 in INDIA any ERP Seconds More Less Expensive **Expensive** Hardware oriented automation **Conventional Single Sensor** no ease of **DPU Analyzer** scalability & maintenance **Less Convenient**


Stainless Steel 304 ULTRA SCAN MILCH AMALYZER

ULTRA SCAN KURIEN



Measuring Range			Accuracy *	Tech. overview	
01.	FAT	00 % - 25 %	± 0.1 %	Sample Volume	20 ml
02.	SNF	03 % - 40 %	<u>±</u> 0.15 %	Sample Temp.	05°c – 40°c
03.	DENSITY	1000 - 1160 kg/m ³	<u>+</u> 0.3 kg/m ³	Humidity	00 % - 80 % RH
04.	CLR (corrected lactometer reading)	00 - 100	<u>+</u> 0.3	Interface	RS 232
05.	PROTIEN	02 % - 15 %	<u>±</u> 0.15 %	Interface	USB
06.	LACTOSE	0.01 % - 20 %	<u>+</u> 0.2 %	Power supply (AC)	95v - 250 v (SMPS)
07.	ADDED WATER	05 % - 99 %	± 03 %	Power Supply (DC)	12 v
08.	FREEZING POINT	0.04°c – 0.70°c	<u>+</u> 0.005°c	Solar Powered	YES (optional)
09.	ADDED SALTS	00 % - 99 %	± 03 %	Dimension	145x210x220 mm
10.	SAMPLE TEMPERATURE	05°c – 40°c	<u>+</u> 01° _c	Enclosure	SS 304
11.	рН	00 - 14	<u>+</u> 0.1	Weight	3.5 kg
12.	CONDUCTIVITY	02 - 14 mS/cm	± 0.1	pH probe	external





Contact Us

P: +91 9359 9359 49

E: info@htindiatech.com

W: www.htindiatech.com

Address: 5, Industrial Estate Ambala Cantt Haryana, India – 133 006